

CONTINUING (1.53(b)) UTILITY PATENT APPLICATION TRANSMITTAL

(Only for continuing applications under 37 CFR 1.53(b))

Attorney Docket No.
522.1919C3

First Named Inventor: Tsutae SHINODA et al.

Title:

FULL COLOR SURFACE DISCHARGE TYPE PLASMA
DEVICE

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent
application contents.ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 53]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 19]
4. ☒ Oath or Declaration [Total Pages: 3]
 - a. ☐ Newly executed (original or copy)
 - b. ☒ Copy from a prior application (37 CFR 1.63(d)) (see Box 18)
5. ☐ This application is filed by fewer than all the inventors named in the prior nonprovisional application.
 - a. ☐ DELETE the following inventor(s) named in the prior nonprovisional application:
 - b. ☐ The inventor(s) to be deleted are set forth on a separate sheet attached hereto.
6. ☒ Incorporation by Reference (usable if Box 4b is checked)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
7. ☐ Microfiche Computer Program (Appendix)
8. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☐ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [] Power of Attorney
11. ☐ English Translation Document (if applicable)
12. ☒ Foreign priority benefit under 35 U.S.C. §119 is claimed.
 - a. ☒ Certified Copy of Priority Document(s) filed in prior application No. 08/496,815.
 - b. ☐ Certified Copy of Priority Document(s) enclosed.
 - c. ☐ Certified Copy of Priority Document(s) to follow.
13. ☒ Information Disclosure Statement (IDS)/PTO-1449 [] Copies of IDS Citations
14. ☒ Preliminary Amendment
 - a. ☒ enclosed herewith.
 - b. ☐ incorporated herein (see Box 18).
15. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
16. ☐ Small Entity Statement(s) [] Statement filed in prior application, status still proper and desired.
17. ☐ Other:

18. CONTINUING APPLICATION, check appropriate box and supply the requisite information below:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: 08/800,759

Prior application information: Examiner: Chow

Group/Art Unit: 2775

* * *

Preliminary Amendment:

☒ Cancel in this application original claims 1-27 of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing purposes.)

☒ Amend the specification by inserting before the first line the sentence:

--This application is a continuation application of application number 08/800,759, filed February 13, 1997, now allowed which, in turn is continuation of application 08/469,815 filed June 6, 1995, now U.S. Patent 5,661,500, which, in turn, is a FWC continuation application of 08/010,169 filed January 28, 1993, now abandoned.--

19. NEW CORRESPONDENCE ADDRESS * CUSTOMER NO. 21,171

21171

PATENT TRADEMARK OFFICE

20. SIGNATURE OF ATTORNEY OR AGENT

| | | | |
|-----------|-------------|------------------|-------------------|
| NAME | H. J. Staas | REGISTRATION NO. | 22,010 |
| SIGNATURE | | DATE | September 5, 2000 |

NEW APPLICATION FEE TRANSMITTAL

Attorney Docket No. 522.1919-C4

Application Number

Filing Date

September 5, 2000

AMOUNT ENCLOSED

\$

690.00

First Named Inventor

Tsutae SHINODA et al.

FEE CALCULATION (fees effective 10/01/97)

| CLAIMS | (1) FOR | (2) NUMBER FILED | (3) NUMBER EXTRA | (4) RATE | (5) CALCULATIONS |
|----------------------------------------------------------------------------------|---------|------------------|------------------|-------------------------------|------------------|
| TOTAL CLAIMS | 17 | - 20 = | 0 | X \$ 18.00 = | \$ 0.00 |
| INDEPENDENT CLAIMS | 3 | - 3 = | 0 | X \$ 78.00 = | 0.00 |
| MULTIPLE DEPENDENT CLAIMS (any number; if applicable) | | | | + \$240.00 = | |
| | | | | BASIC FILING FEE | 690.00 |
| | | | | Total of above Calculations = | \$ 690.00 |
| Surcharge for late filing fee, Statement or Power of Attorney (\$130.00) | | | | + | 0.00 |
| Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28). | | | | - | 0.00 |
| | | | | TOTAL FILING FEE = | \$ 690.00 |
| Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d)) | | | | + | 0.00 |
| Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1)) | | | | + | |
| | | | | TOTAL FEES DUE = | \$ 690.00 |

METHOD OF PAYMENT

- ☒ Check enclosed as payment.
- ☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
- ☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

GENERAL AUTHORIZATION

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.


19-3935

Deposit Account Name

STAAS & HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

SUBMITTED BY: STAAS & HALSEY LLP

| | | | |
|------------|-------------------------------------------------------------------------------------|----------|-------------------|
| Typed Name | H. J. Staas | Reg. No. | 22,010 |
| Signature |  | Date | September 5, 2000 |

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Tsutae SHINODA et al.

Group Art Unit:

Application No.:

Examiner:

Filed: September 5, 2000

For: FULL COLOR SURFACE DISCHARGE TYPE PLASMA DISPLAY DEVICE

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Before examination of the above-identified application, please amend the application as follows:

IN THE CLAIMS

Please CANCEL claims 1-17 and ADD the following NEW claims 28-45

28. (NEW) A discharge cell of a surface discharge type plasma display panel, comprising:

a cavity bounded by respective opposing and spaced sidewalls of a pair of barriers, formed on a first substrate, extending commonly with the pair of barriers in a first direction; an address electrode on the first substrate, at the bottom of the cavity, and extending in the first direction;

a pair of display electrodes formed on a surface of a second substrate, covered by an insulating layer and positioned in opposed relationship with the address electrode, the pair of display electrodes extending in a second direction, transversely to and crossing the barriers and the cavity therebetween, and defining the discharge cell; and

005060-26845950

a phosphor layer disposed within the cavity on one of the first and second substrates, the phosphor layer having a thickness in a range of from 10 μm to 50 μm .

29. (NEW) A discharge cell as recited in claim 28, wherein the phosphor layer is formed on the first substrate, aligned within the cavity, and covers the entire surface of the cavity including sidewalls of the pair of barriers and thereby to constitute a discharge cell of a reflecting type plasma display panel.

30. (NEW) A discharge cell as recited in claim 28, wherein the pair of display electrodes has a discharge gap of a first width at a central portion of a unit luminescent area and a gap of a second, greater width, at both end portions of the unit luminescent area.

31. (NEW) A discharge cell as recited in claim 28, wherein a top portion of each barrier is of a dark color.

32. (NEW) A discharge cell as recited in claim 29, wherein a top portion of each barrier is of a dark color.

33. (NEW) A discharge cell as recited in claim 28, wherein a width of each cell, in the second direction, is approximately one-third a length thereof, in the first direction.

34. (NEW) A discharge cell as recited in claim 28, wherein each of the pair of display electrodes comprises a metal conductor extending in the second direction, transverse to the first direction and the pair of spaced barriers, the pair of metal conductors having a combined width in the first direction which is limited so as not to block more than 21 % of light emitted from the discharge cell.

35. (NEW) A plasma display panel of a surface discharge type and having an array, of plural columns in the first direction and plural rows in a second direction transverse to the first direction, of plural image elements, each image element comprising a respective set of

09654893.090508
005060" 05345960

unit luminescent areas, each area comprising a set of discharge cells, wherein each discharge cell comprises:

a cavity bounded by respective opposing and spaced sidewalls of a pair of barriers formed on a first substrate, the cavity extending commonly with the pair of barriers in a first direction;

an address electrode on the first substrate, extending in the first direction,

a pair of display electrodes formed on a surface of a second substrate covered by an insulating layer and positioned in opposed relationship with the barriers, the pair of display electrodes extending in a second direction, transversely to and crossing the barriers and the cavity therebetween, and defining the discharge cell, and

a phosphor layer disposed within the cavity on the first substrate; and

each set of discharge cells comprises a common number of discharge cells in successively spaced adjacent positions in the second direction, the respective phosphor layers of each set of the discharge cells being in a common sequence of respective, different colors, and the plural rows of the array having respective, common numbers of sets of discharge cells, aligned in the columns of the array.

36. (NEW) A plasma display panel as recited in claim 35, wherein:

each set of discharge cells has respective, first and second combined dimensions in the first and second directions which are substantially the same.

37. (NEW) A plasma display panel as recited in claim 35, wherein:

each set of discharge cells comprises plural cells having plural, respective and different color phosphor layers, each of which layers having a thickness in a range of from 10 μm to 50 μm .

38. (NEW) A plasma display panel as recited in claim 35, wherein:

the plural cells of each set are of a common width in the second direction.

39. (NEW) A plasma display panel as recited in claim 35, wherein:

the plural cells of each set are of respective, different widths in the second direction.

40. (NEW) A plasma display panel as recited in claim 35 wherein, in each discharge cell, the phosphor layer covers the respective, opposing sidewalls of the pair of barriers.

41. (NEW) A plasma display panel as recited in claim 35 wherein, in each discharge cell, the phosphor layer is formed on the first substrate, aligned within the cavity, and covers the address electrode and extends to the respective, opposing sidewalls of the pair of barriers, said phosphor layer having a thickness in a range of from 10 μm to 50 μm .

42. (NEW) A plasma display panel recited in claim 35, wherein each of the pair of display electrodes of each discharge cell comprises a transparent conductor and a respective metal conductor extending therewith in the second direction, and the pair thereof provides a predetermined discharge gap at a central portion of the cell.

43. (NEW) A plasma display panel as recited in claim 35 wherein, in each discharge cell, the phosphor layer is formed within the cavity and extends to the respective, opposing sidewalls of the barriers and a top portion of each of the barriers has a dark color.

44. (NEW) A plasma display panel as recited in claim 35, wherein each of the pair of display electrodes comprises a metal conductor extending in the second direction, transverse to the first direction and the pair of spaced barriers, the pair of metal conductors having a combined width in the first direction which is limited so as not to block more than 21 % of light emitted from the discharge cell.

45. (NEW) A plasma display panel of a surface discharge type and having an array of plural image elements, arranged in plural columns in a first direction and plural rows in a second direction, transverse to the first direction, wherein each image element comprises a respective set of unit luminescent areas:

each unit luminescent area comprises:

a cavity, bounded by respective opposing and spaced sidewalls of barriers formed on a first substrate and extending in the first direction,

an address electrode of the first substrate extending in the first direction,

a pair of display electrodes formed on a second substrate, covered by a dielectric layer and arranged to constitute a corresponding row of the array in opposed relationship with the cavity, and

a phosphor layer disposed on an inside surface of the cavity on the first substrate with a thickness in a range of 10 μm -50 μm ; and

each set of unit luminescent areas comprises a common number of unit luminescent areas in successively spaced adjacent positions in the second direction, the respective phosphor layers of each set of unit luminescent areas being in a common sequence of respective, different colors, and the plural rows of the array having respective, common numbers of sets of unit luminescent areas, aligned in the columns of the array.

REMARKS

This Preliminary Amendment is submitted to obtain protection for structures of a discharge cell and of a plasma display panel incorporating such discharge cells in accordance with the present invention and as defined by the foregoing claims. No new matter is presented.

It is respectfully requested that this Preliminary Amendment be entered in the above-referenced application.

If any further fees are required in connection with the filing of this Preliminary Amendment, please charge same to our Deposit Account No. 19-3935.

Respectfully submitted,

STAAS & HALSEY LLP

Date: September 5, 2000

By: _____


H. J. Staas

Registration No. 22,010

700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001
Telephone: (202) 434-1500
Facsimile: (202) 434-1501

FULL COLOR SURFACE DISCHARGE
TYPE PLASMA DISPLAY DEVICE

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to a surface discharge type full color surface discharge type plasma display panel and a process for manufacturing the same. More specifically, the present invention relates to a full color ac plasma display device high in resolution and brightness of display such that it is adaptable to a high quality display, such as a high definition TV, and can be used in daylight.

2. Description of the Related Art

15 A plasma display panel (PDP) has been considered the most suitable flat display device for a large size, exceeding over 20 inches, because a high speed display is possible and a large size panel can easily be made. It is also considered to be adaptable to a high definition TV. Accordingly, an improvement in full color display capability in plasma display panels is desired.

20 In the past, two electrode type dc and ac plasma display panels have been proposed and developed. Also, a surface discharge type ac plasma display panel, among other plasma display panels, has been known to be suitable for a full color display.

25 For example, a surface discharge type ac plasma display panel having a three electrode structure comprises a plurality of parallel display electrode pairs formed on a substrate and a plurality of address electrodes perpendicular to the display electrode pairs for selectively illuminating unit luminescent areas. Phosphors are arranged,

in order to avoid damage by ion bombardment, on the other substrate facing the display electrode pairs with a discharge space between the phosphor and the display electrode pairs and are excited by ultra-violet rays generated from a surface discharge between the display electrodes, thereby causing luminescence. See for example, U. S. Patent No. 4,638,218 issued on January 20, 1987 and No. 4,737,687 issued on April 12, 1988.

The full color display is obtained using an adequate combination of three different colors, such as red (R), green (G) and blue (B), and an image element is defined by at least three luminescent areas corresponding to the above three colors.

Conventionally, an image element is composed of four subpixels arranged in two rows and two columns, including a first color luminescent area, for example, R, a second color luminescent area, for example, G, a third color luminescent area, for example, G, and a fourth color luminescent area, for example, B. Namely, this image element comprises four luminescent areas of a combination of three primary colors for additive mixture of colors and an additional green having a high relative luminous factor. By controlling the additional green area independent from the other three luminescent areas, an apparent image element number can be increased and thus an apparent higher resolution or finer image can be obtained.

In this arrangement of four subpixels, two pairs of display electrodes cross an image element, i.e., each pair of display electrodes crosses each row or column of subpixels, which is apparently disadvantageous in making image elements finer.

If the image elements are to be finer, formation of finer display electrodes becomes difficult and the drive voltage margin for avoiding interference of discharge

between different electrode lines becomes narrow. Moreover,
the display electrodes become narrower, which may cause
damage to the electrodes. Further, a display of one image
element requires time for scanning two lines, which may make
5 a high speed display operation difficult because of the
frequency limitation of a drive circuit.

The present invention is directed to solve the above
problem and provide a flat panel full color surface
discharge type plasma display device having fine image
10 elements.

JP-A-01-304638, published on December 8, 1989,
discloses a plasma display panel in which a plurality of
parallel barriers are arranged on a substrate and
luminescent areas, in the form of strips defined by the
15 parallel barriers, are formed. This disclosure is, however,
directed only to two electrode type plasma display panels,
not to a three electrode type plasma display panel in which
parallel display electrode pairs and address electrodes
intersecting the display electrode pairs are arranged and
20 three luminescent areas are arranged in the direction of the
extending lines of the display electrode pairs as in the
present invention.

The present invention is also directed to a plasma
display panel exhibiting a high image brightness at a wide
view angle range. In this connection, U.S. Patent No.
25 5,086,297 issued on February 4, 1992, corresponding to
JP-A-01-313837 published on December 19, 1989, discloses a
plasma display panel in which phosphors are coated on side
walls of barriers. Nevertheless, in this plasma display
30 panel, the phosphors are coated selectively on the side
walls of barriers and do not cover the flat surface of the
substrate on which electrodes are disposed.

SUMMARY OF THE INVENTION

To attain the above and other objects of the present invention, there is provided a full color surface discharge type plasma display device comprising pairs of lines of display electrodes (X and Y), each pair of lines of display electrodes being parallel to each other and constituting an electrode pair for surface discharge; lines of address electrodes (22 or A) insulated from the display electrodes and running in a direction intersecting the lines of display electrodes; three phosphor layers (28R, 28G and 28B), different from each other in respective luminescent colors, facing the display electrodes and arranged in a successive order of the three phosphor layers along the extending lines of the display electrodes, and a discharge gas in a space (30) between said display electrodes and said phosphor layers, wherein the adjacent three phosphor layers (28R, 28G and 28B) (EU) of said three different luminescent colors and a pair of lines of display electrodes define one image element (EG) of a full color display.

In accordance with the present invention, there is also provided a full color surface discharge plasma display device comprising first and second substrates facing and parallel to each other for defining a space in which a discharge gas is filled; pairs of lines of display electrodes formed on the first substrate facing the second substrate, each pair of lines of display electrodes being parallel to each other and constituting an electrode pair for surface discharge; a dielectric layer over the display electrodes and the first substrate; lines of address electrodes formed on the second substrate facing the first substrate and running in a direction intersecting the lines of display electrodes; three phosphor layers, different from each other in respective luminescent colors, formed on the second substrate in a successive order of said three

luminescent colors along the extending lines of the display electrodes, the phosphor layers entirely covering the address electrodes; and barriers standing on the second substrate to divide and separate said discharge space into
5 cells corresponding to respective phosphor layers, the barriers having side walls; wherein the adjacent three phosphor layers of said three different luminescent colors and a pair of lines of display electrodes define one image element of a full color display and said phosphor layers
10 extend to the side walls of said barriers to cover almost the entire surfaces of the side walls of said barriers.

In accordance with a preferred embodiment of the present invention, there is provided a full color surface discharge plasma display device comprising first and second
15 substrates facing and parallel to each other for defining a space in which a discharge gas is filled, the first substrate being disposed on a side of a viewer; pairs of lines of display electrodes formed on the first substrate facing the second substrate, each pair of lines of display electrodes being parallel to each other and constituting an
20 electrode pair for surface discharge, each of the display electrodes comprising a combination of a transparent conductor line and a metal line in contact with said transparent conductor line and having a width narrower than that of the transparent conductor line; a dielectric layer
25 over the display electrodes and the first substrate; lines of address electrodes formed on the second substrate facing the first substrate and running in a direction intersecting the lines of display electrodes; barriers standing on the second substrate, in parallel to said address electrodes,
30 for dividing said discharge gas space into cells, the barriers having side walls; and three phosphor layers, different from each other in respective luminescent colors formed on the second substrate in a successive order of said

three luminescent colors along the extending lines of the display electrodes, the phosphor layers entirely covering the address electrodes and extending to the side walls of said barriers to cover almost the entire surfaces of the side walls of said barriers; wherein the adjacent three phosphor layers of said three different luminescent colors and a pair of lines of display electrodes define one image element of a full color display.

To protect the phosphor provided over the address electrode from ion bombardment, the following drive can be adopted. First, an erase address type drive control system in which once all image elements corresponding the pair of to the display electrodes are written, an erase pulse is applied to one of the pair of the display electrodes and simultaneously an electric field control pulse for neutralizing or cancelling the applied erase pulse is selectively applied to the address electrodes.

Second, a write address type drive control system is provided in which in displaying a line corresponding to a pair of the display electrodes, a discharge display pulse is applied to one of the pair of the display electrodes and simultaneously an electric field control pulse for writing is selectively applied to the address electrodes. This write address type drive control system is preferably constituted such that in displaying a line corresponding to a pair of the display electrodes, once all image elements corresponding to the display electrodes are subject to writing and erasing discharges, to store positive electric charges above said phosphor layers and negative electric charges above said insulating layer, an electric discharge display pulse is applied to one of the pair of the display electrodes to make said one of the pair of the display electrodes negative in electric potential to the other of the pair of the display electrodes, and an electric

discharge pulse is selectively applied to the address electrodes to make the address electrodes positive in electric potential relatively to said one of the pair of the display electrodes.

5 It is preferred in the above full color surface discharge plasma display device that the image element has an almost square area and each of the three phosphor layers has a rectangular shape that is obtained by dividing the square of the image element and is long in a direction
10 perpendicular to the lines of display electrodes. Additionally, it is preferred that each of the lines of the display electrodes comprises a combination of a transparent conductor line and a metal line in contact with the transparent conductor line and having a width narrower than
15 that of the transparent conductor line and is disposed on the side of a viewer compared with the phosphor layers; the transparent conductor lines have partial cutouts in such a shape that the surface discharge is localized to a portion between the display electrodes without the cutout in each
20 unit luminescent area; the total width of a pair of the display electrodes and a gap for discharge formed between the pair of the display electrodes is less than 70% of a pitch of the pairs of display electrodes; the device further comprises barriers standing on a substrate and dividing and separating the space between the display electrodes and the
25 phosphor layers into cells corresponding to respective phosphor layers; the barriers have side walls and the phosphor layers extend to and almost entirely cover the side walls of the barriers; the address electrodes exist on a
30 side of the substrate opposite to the display electrodes and the address electrodes are entirely covered with the phosphor layers; the device further comprises a substrate and a underlying layer of a low melting point glass containing a light color colorant formed on the substrate

and the address electrodes are formed on the underlying layer; at least part of the barriers comprises a low melting point glass containing a light color colorant; and the barriers comprise a low melting point glass containing a dark color colorant in a top portion thereof and a low melting point glass admixed with a light color colorant in the other portion.

In accordance with the present invention, there is also provided a process for manufacturing a full color surface discharge plasma display device as above, in which the address electrodes and the barriers are parallel to each other and the address electrodes comprise a main portion for display parallel to the barriers and a portion at an end of said main portion for connecting to outer leads, the process comprising the steps of printing a material for forming the main portions of the address electrodes using a printing mask, printing a material for forming the outer lead-connecting portions, and printing a material for forming the barriers using the printing mask used for printing the material for forming the main portions of the address electrodes.

Further, there is also provided a process for manufacturing a full color surface discharge type plasma display device as above. This process comprises the steps of forming the barriers on the second substrate, almost filling gaps between the barriers above the second substrate with a phosphor paste, firing the phosphor paste to reduce the volume of the phosphor paste and form recesses between the barriers and to form a phosphor layer covering almost the entire surfaces of side walls of the barriers and covering surfaces of the second substrate between the barriers.

It is preferred that the phosphor paste comprise 10 to 50% by weight of a phosphor and the filling of the phosphor

paste be performed by screen printing the phosphor paste into the spaces with a square squeezer at a set angle of 70 to 85 degrees.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Fig. 1 schematically shows the basic construction of a full color surface discharge type plasma display device of the present invention;

 Fig. 2 is a perspective view of a full color flat panel ac plasma display device of the present invention;

10 Fig. 3A shows a first structure of plasma display devices of the prior art;

 Fig. 3B shows a second structure of plasma display devices of the prior art;

15 Fig. 4 shows a third structure of plasma display devices of the prior art;

 Fig. 5 shows a first operation of plasma display devices of the prior art;

 Fig. 6 shows a fourth structure of plasma display devices of the prior art;

20 Fig. 7 is one perspective view of another full color flat panel ac plasma display device of the present invention;

25 Fig. 8 is a second perspective view of another full color flat panel ac plasma display device of the present invention;

 Fig. 9 is a first graph illustrating the brightness of display versus the view angle;

 Fig. 10 is a second graph illustrating the brightness of display versus the view angle;

30 Fig. 11 is a first graph to illustrate how the stability of the discharge varies based on the structures of the barriers;

Fig. 12 is a second graph to illustrate how the stability of the discharge varies based on the structures of the barriers;

Fig. 13 is a third graph to illustrate how the stability of the discharge varies based on the structures of the barriers;

Fig. 14 is a block diagram of a full color flat panel ac plasma display device of an embodiment of the present invention;

Fig. 15 schematically shows the arrangement of the electrodes of the plasma display panel, as in Fig. 14;

Fig. 16 shows the waveform of the addressing voltage of a full color flat panel ac plasma display device in an embodiment of the present invention;

Fig. 17 is a block diagram of a full color flat panel ac plasma display device of another embodiment of the present invention;

Fig. 18 shows the waveform of the addressing voltage of a full color flat panel ac plasma display device in another embodiment of the present invention;

Figs. 19A to 19H show the state of the electric charges at main stages in the operation in accordance with the waveform of the addressing voltage of Fig. 18;

Fig. 20 shows an ideal coverage of a phosphor layer on barriers and a substrate;

Fig. 21 shows the relationship between the thickness of the phosphor layer and the content of phosphor in a phosphor paste;

Figs. 22A to 22C are cross-sectional views, used as an aid for understanding the main steps of forming a phosphor layer in a preferred embodiment of the present invention;

Fig. 23 is a perspective view of a flat panel ac plasma display device;

Figs. 24A and 24B are planar views, used as an aid for understanding the steps of forming address electrodes and barriers on a glass substrate in the prior art; and

Figs. 25A to 25F are planar and segmented views, used as an aid for understanding the steps of forming address electrodes and barriers on a glass substrate in a preferred embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Before describing the present invention in more detail, the prior art is described with reference to drawings so as to understand the present invention more clearly.

Figs. 3A and 3B show the basic respective constructions of dc and ac two electrode plasma display panels. These constructions of two electrode plasma display panels appear in Figs. 5 and 6 of JP-A-01-304638. In Fig. 3A of the present application, i.e., an opposite discharge type dc plasma display panel, two substrates 51 and 52 are faced parallel to each other. Gas discharge cells 53 are defined by straight cell barriers 54 and the two substrates 51 and 52. A discharge gas exists in the discharge cells 53. An anode 55 is formed on a substrate 51 on the side of the viewer. A cathode 56 is formed on the other substrate 52. A phosphor layer 57, in the form of strip, is formed on the substrate 51, such that the anode 55 and the phosphor layer 57 do not overlap each other. When a dc voltage is applied between the anode 55 and the cathode 56, an electric discharge emitting ultra-violet rays occurs in the discharge cell 53, which illuminates the phosphor layer 57. Separating the phosphor layer 57 from the anode 55 is to prevent damages of the phosphor layer by ion bombardment due to the discharge, since if the phosphor layer overlaps the anode 55, ion bombardment of the anode damages the phosphor layer on the anode 55.

005060" E6245960

This conventional panel is an opposite discharge type and different from the surface discharge type of the present invention. Although the phosphors and barriers are straight or in the form of strips, the opposite electrodes are arranged to intersect with each other and the phosphors extend in the direction of one of the extending lines of the opposite electrodes. In the opposite discharge type plasma display panel, ions generated during the discharge bombard and deteriorate the phosphors, thereby shortening the life of the panel. In contrast, in a three electrode surface discharge type panel, discharge occurs between the parallel display electrode pairs formed on one substrate, which prevents deterioration of the phosphor disposed on the other side substrate.

Fig.3B, i.e., a surface discharge type ac plasma display device, two substrates 61 and 62 are faced parallel to each other. Gas discharge cells 63 are defined by straight cell barriers 64 and the two substrates 61 and 62. A discharge gas exists in the discharge cells 63. Two electrodes 65 and 66, arranged normal to each other in plane view, are formed on the substrate 62 with a dielectric layer 67 therebetween. A second dielectric layer 68 and a protecting layer 69 are stacked on the dielectric layer 67. A phosphor layer 70 is formed as a strip on the substrate 61. When an electric field is applied between the two electrodes 65 and 66, a discharge generating ultraviolet rays occurs, which illuminates the phosphor layer 70.

In this conventional surface discharge type panel, the straight barriers and the strip phosphors are parallel to each other, but the pair of display electrodes are arranged to intersect with each other and the phosphors extend in the direction of one of the display electrode pair. In contrast, the three different luminescent color phosphors are arranged

in the extending direction of the parallel display electrode pairs.

This conventional surface discharge type panel has several disadvantages. Selection of the materials of the X and Y display electrodes is difficult since the two electrode layers X and Y are stacked upon each other (as a dielectric layer disposed between the two display electrodes is made of a low melting point glass, failure of the upper electrode on the low melting point glass or a short circuit may occur when the low melting point glass is fired). Additionally, a protecting layer at the cross section (i.e., intersection) of the X and Y display electrodes is damaged by discharge due to the electric field concentration there, which causes variation of the discharge voltage. Further, a large capacitance caused by the stack of the two electrodes on one substrate results in disadvantageous drive. As a result of these disadvantages, this type of panel has never been put into practical use.

Also known is a three electrode type surface gas discharge ac plasma display panel as shown in Fig. 4. A display electrode pair X_j and Y_j , each comprising a transparent conductor strip 72 and a metal layer 73, are formed on a glass substrate 71 on the display surface side H. A dielectric layer 74 for an ac drive is formed on the substrate 71 to cover the display electrodes X_j and Y_j . A first barrier 75 in the form of a cross lattice, defining a unit luminescent area EU_j , is formed on the glass substrate 71. Parallel second barriers 76, corresponding to the vertical lines of the barrier 75, are formed on a glass substrate 79 so that discharge cells 77 are defined between the substrates 71 and 79 by the first and second barriers 75 and 76. An address electrode A_j and a phosphor layer 78 are formed on the substrate 79. The address electrode A_j , which selectively illuminates the unit luminescent area EU, and

the phosphor layer 78 intersects the display electrode pair Xj and Yj. The address electrode Aj is formed adjacent to the one side barrier 76 and the phosphor layer 78 is adjacent to the other side barrier 76. The address electrode Aj may be formed on the side of the substrate 71, for example, below the display electrode pairs Xj and Yj with a dielectric layer therebetween.

In this ac plasma discharge panel, erase addressing, in which writing (formation of a stack of wall charges) of a line L is followed by selective erasing, and a self-erase discharge is utilized for selective erasing, is typically used.

More specifically, referring to Figs. 4 and 5, in an initial address cycle CA of a line display period T corresponding to one line display, a positive writing pulse PW having a wave height Vw is applied to display electrodes Xj, which corresponds to a line to be displayed. Simultaneously, a negative discharge sustain pulse having a wave height Vs is simultaneously applied to a display electrode Y corresponding to the line to be displayed. In Fig. 5, the inclined line added to the discharge sustain voltage PS indicates that it is selectively applied to respective lines.

At this time, a relative electrical potential between the display electrodes Xj and Yj, i.e., a cell voltage applied to the surface discharge cell, is above the firing voltage; therefore, surface discharge occurs in all surface discharge cells C corresponding to one line. By the surface discharge, wall charges, having polarities opposite to those of the applied voltage, are stacked on the protecting layer 18 and, accordingly, the cell voltage is lowered to a predetermined voltage at which the surface discharge stops. The surface discharge cells are then in the written state.

Next, a discharge sustain pulse PS is alternately applied to the display electrodes Xj and Yj, and by superimposing the voltage Vs of the discharge sustain pulse PS onto the wall charges, the cell voltages then become the above firing voltage and surface discharge occurs every time one of the discharge sustain pulses PS is applied.

After the written state is made stable by a plurality of surface discharges, at an end stage of the address cycle CA, a positive selective discharge pulse PA having a wave height Va is applied to address electrodes corresponding to unit luminescent areas EU to be made into a non-display state in one line. Simultaneously, the discharge sustain pulse PS is applied to the display electrode Yj, to erase the wall charges unnecessary for display (selective erase). In Fig. 5, the inclined line added to the selective discharge pulse PA indicates that it is selectively applied to each of the unit luminescent areas EU in one line.

At a rising edge of the selective discharge pulse PA, an opposite discharge occurs at an intersection between the address electrode Aj and the display electrode Yj in the direction of the gap of the discharge space 30 between the substrates 11 and 21. By this discharge, excess wall charges are stacked in surface discharge cells and when the selective discharge pulse PA is lowered and the discharge sustain pulse PS is raised, a discharge due to the wall charges only occurs (self-erase discharge). The self-erase discharge has a short discharge sustain time since no discharge current is supplied from the electrodes. Accordingly, the wall charges disappear in the form of neutralization.

In the following display cycle CH, the discharge sustain voltage PS is alternately applied to the display electrodes Xj and Yj. At every rising edge of the discharge sustain voltage PS, only the surface discharge cells C in

which the wall charges are not lost are subject to discharge, by which ultra-violet rays are irradiated to excite and illuminate the phosphor layers 28. In the display cycle CH, the period of the discharge sustain voltage PS is selected so as to control the display brightness.

The above operation is repeated for every line display period T and the display is performed for respective lines.

It is noted that it is possible for the writing to be performed simultaneously for all lines followed by line-by-line selective erasing of wall discharges, so that the writing time in an image display period (field) is shortened and the operation of display is sped up.

In this three electrode type ac plasma discharge panel, the selection of the discharge cell for electric discharge is memorized and the power consumption for display or sustainment of discharge can be lowered. Second, the electric discharge occurs near the surface of the protecting layer on the display electrode pair X_j and Y_j so that damage of the phosphor layer by ion bombardment can be prevented, particularly when the phosphor layer and the address electrode are separated.

Fig. 6 shows a typical arrangement of three different color phosphor layers for a full color display in a three electrode type ac plasma discharge panel. In Fig. 6, EG denotes an image element, EU_j denotes a unit luminescent area, R denotes a unit luminescent area of red, G denotes a unit luminescent area of green, B denotes a unit luminescent area of blue, and X_j and Y_j denote a pair of display electrodes, respectively.

As seen in Fig. 6, one display line L is defined by the pair of display electrodes X_j and Y_j , and each image element EG is composed of four unit luminescent areas EU_j of two rows and two columns, to which two lines L, i.e., four display electrodes X_j and Y_j correspond. In an image element

EG, the left upper unit luminescent area EUj is a first color, e.g. R, the right upper and left lower unit luminescent areas EUj are a second color, e.g. G, and the right lower unit luminescent area EUj is a third color, e.g.

5 B. More specifically, the image element EG includes a combination of unit luminescent areas EUj of the three primary colors for mixture of additive colors. EG also includes an additional unit luminescent area EUj of green having a high relative luminous factor. The additional unit
10 luminescent area EUj of green permits an increase in the apparent number of image elements by independent control thereof from the other three unit luminescent areas EUj.

In this arrangement of the unit luminescent areas EUj, as described before, the four display electrodes required in
15 an image element are disadvantageous in making the image elements finer. First, the formation of a fine electrode pattern has a size limitation. Second, if the gap between the display lines L is too narrow, a margin for preventing an interference between discharges on the display lines
20 becomes too small. Third, if the width of the display electrodes is too narrow, the display electrodes tend to be broken or cut. Fourth, a display of an image element requires time for scanning two lines L, which may make a high speed display operation difficult, particularly when a
25 panel size or image element number is increased.

In accordance with the present invention, with reference to Figs. 1 and 2, the above problems are solved by a display device comprising pairs of lines of display electrodes X and Y; lines of address electrodes 22 insulated
30 from the display electrodes X and Y and running in a direction intersecting the lines of display electrodes X and Y; areas of three phosphor layers 28R, 28G and 28B different from each other in luminescent color, facing the display electrodes and arranged in a successive order of the three

phosphor layers along the extending lines of the display electrodes X and Y; and a discharge gas in a space 30 between the display electrodes X and Y and the phosphors, such that the adjacent three phosphor layers EU of the three different luminescent colors 28R, 28G and 28B and a pair of lines of display electrodes X and Y define one image element EG of a full color display.

In this construction, only one display electrode pair, i.e., two display electrodes, is arranged in one image element. Accordingly, it is possible to reduce the size of the image elements. Also, it is possible to increase the area where display electrodes do not cover an image element so that the brightness of the display can be increased since metal electrodes interrupt illumination from the phosphors.

Fig. 1 is a plane view of an arrangement of display electrodes X and Y in an image element EG and Fig. 2 is a schematic perspective view of a structure of an image element.

Referring to Fig. 2, a three electrode type surface gas discharge ac plasma display panel is shown that comprises a glass substrate 11 on the side of the display surface H; a pair of display electrodes X and Y extending transversely parallel to each other; a dielectric layer 17 for an ac drive; a protecting layer 18 of MgO; a glass substrate 21 on the background side; a plurality of barriers extending vertically and defining the pitch of discharge spaces 30 by contacting the top thereof with the protecting layer 18; address electrodes 22 disposed between the barriers 29; and phosphor layers 28R, 28G and 28B of three primary colors of red R, green G and blue B.

The discharge spaces 30 are defined as unit luminescent areas EU by the barriers 29 and are filled with a Penning gas of a mixture of neon with xenon (about 1 - 15 mole %) at a pressure of about 500 Torr as an electric discharge gas

emitting ultra-violet rays for exciting the phosphor layers 28R, 28G and 28B.

In Fig. 2, the barriers 29 are formed on the side of the substrate 21 but are not formed on the side of the substrate 11, which is advantageous in accordance with the present invention and described in more detail later.

Each of the display electrodes X and Y comprises a transparent conductor strip 41, about 180 μm wide, and metal layer 42, about 80 μm wide, for supplementing the conductivity of the transparent conductor strip 41. The transparent conductor strip 41 are, for example, a tin oxide layer and the metal layers 42 are, for example, a Cr/Cu/Cr three sublayer structure.

The distance between a pair of the display electrodes X and Y, i.e., the discharge gap, is selected to be about 40 μm and an MgO layer 18 about a few hundred nano meters thick is formed on the dielectric layer 17. The interruption of a discharge between adjacent display electrode pairs, or lines, L can be prevented by providing a predetermined distance between the adjacent display electrode pairs, or lines, L. Therefore, barriers for defining discharge cells corresponding to each line L are not necessary. Accordingly, the barriers may be in the form of parallel strips, not the cross lattice enclosing each unit luminescent area, as shown in Fig. 3, and thus, can be very much simplified.

The phosphors 28R, 28G and 28B are disposed in the order of R, G and B from the left to the right to cover the surfaces of the substrate 21 and the barriers 29 defining the respective discharge spaces there-between. The phosphor 28R emitting red luminescence is of, for example, $(\text{Y}, \text{Gd})\text{BO}_3:\text{Eu}^{2+}$, the phosphor 28G emitting green luminescence is of, for example, $\text{Zn}_2\text{SiO}_4:\text{Mn}$, and the phosphor 28B emitting blue luminescence is of, for example, $\text{BaMgAl}_{14}\text{O}_{23}:\text{Eu}^{2+}$. The compositions of the phosphors 28R, 28G

and 28B are selected such that the color of the mixture of luminescences of the phosphors 28R, 28G and 28B when simultaneously excited under the same conditions is white.

At an intersection of one of a pair of display electrodes X and Y with an address electrode 22, a selected discharge cell, not indicated in the figures, for selecting display or non-display of the unit luminescent area EU is defined. A primary discharge cell, not indicated in the figures, is defined near the selected discharge cell by a space corresponding to the phosphor. By this construction, a portion, corresponding to each unit luminescent area EU, of each of the vertically extending phosphor layers 28R, 28G and 28B can be selectively illuminated and a full color display by a combination of R, G and B can be realized.

Referring to Fig. 1, respective image elements are comprised of three unit luminescent areas EU arranged transversely and having the same areas. The image elements advantageously have the shape of a square for high image quality and, accordingly, the unit luminescent areas EU have a rectangular shape elongated in the vertical direction, for example, about $660\text{ }\mu\text{m}$ x $220\text{ }\mu\text{m}$.

A pair of display electrodes are made corresponding to each image element EG, namely, one image element EG corresponds to one line L.

Accordingly, in comparison with the case of the prior art as shown in Fig. 3 where two lines L correspond to one image element EG, the number of the electrodes in an image element EG is reduced by half in the construction of the present invention as shown in Figs. 1 and 2, as compared to the prior art of Figs. 3 and 4.

If the area of one image element EG is selected to be the same as that of the prior art, the width of the display electrodes X and Y can be almost doubled. As the width of the display electrodes X and Y is larger, the reliability is

increased since the probability of breaking the electrodes is reduced.

Further, the width of the transparent conductor strip 41 can be made sufficiently large, compared to the width of the metal layer 42 that is necessarily more than a predetermined width to ensure the conductivity over the entire length of the line L. This allows an increase in the effective area of illumination and thus the display brightness.

For example, in the arrangement of Fig. 3, the width of the display electrodes X_j and Y_j is $90\text{ }\mu\text{m}$, the gap between a pair of the display electrodes X_j and Y_j is $50\text{ }\mu\text{m}$, and the width of the unit luminescent area EU_j is $330\text{ }\mu\text{m}$. The gap between a pair of display electrodes X_j and Y_j of at least $50\text{ }\mu\text{m}$ is necessary to ensure a stable initiation of discharge and a stable discharge. A width of the display electrodes X_j and Y_j of $90\text{ }\mu\text{m}$ is selected because a metal layer having at least a $70\text{ }\mu\text{m}$ width is necessary to ensure conductivity for a 21 inch (537.6mm) line L or panel length. Moreover, the total width of the pair of display electrodes X_j and Y_j and the gap therebetween should be not more than about 70% of the width of the unit luminescent area EU_j , as determined in accordance with the present invention. Accordingly, in an image element EG having a total width of $330\text{ }\mu\text{m} \times 2 = 660\text{ }\mu\text{m}$, the total width of four display electrodes X_j and Y_j is $90\text{ }\mu\text{m} \times 4 = 360\text{ }\mu\text{m}$ and the total width of the four metal layers in the display electrodes X_j and Y_j is $70\text{ }\mu\text{m} \times 4 = 280\text{ }\mu\text{m}$. The total width of the metal layers is $70\text{ }\mu\text{m} \times 4 = 280\text{ }\mu\text{m}$ and the effective illumination area is $(660\text{ }\mu\text{m} - 280\text{ }\mu\text{m}) = 380\text{ }\mu\text{m}$, 58% of the image element.

In comparison with the above, in the construction as shown in Figs. 1 and 2, if the total width of the image element EG is selected to be the same as above, i.e., $660\text{ }\mu\text{m}$, the total width of the pair of display electrodes X and Y

and the gap therebetween can be $460\ \mu\text{m}$, the gap between a pair of the display electrodes X and Y is $50\ \mu\text{m}$, and accordingly, the width of each of the display electrodes X and Y is $210\ \mu\text{m}$ including the width of the metal layer 42 of $70\ \mu\text{m}$ and the rest width of the transparent conductor strip 41 of $140\ \mu\text{m}$. The width of each display electrode of $210\ \mu\text{m}$ is 233% of the width of the prior art of $90\ \mu\text{m}$. The total width of the metal layers 42 is only $70\ \mu\text{m} \times 2 = 140\ \mu\text{m}$ and the effective illumination area is $(660\ \mu\text{m} - 140\ \mu\text{m}) = 520\ \mu\text{m}$, 79% of the image element, which is about 138%, compared to that of the prior art, which is 58%.

Of course, although the size of an image element is made the same in the above comparison, it is possible in the present invention for the size of an image element to be decreased without the risk of the display electrodes breaking and a very fine display can easily be attained.

Further, although the above is a so-called reflecting type panel in which the phosphor layers 28R, 28G and 28B are disposed on the background side glass substrate 21, the present invention may also be applied to a so-called transmission type panel in which the phosphor layers 28R, 28G and 28B are disposed on the display surface side glass substrate 11.

Referring back to Fig. 4, a gap of the discharge cells 77 between the two substrates 71 and 79 or the total height of the barriers 75 and 76 is generally selected to about 100 to $130\ \mu\text{m}$ for alleviating the shock by ion bombardment during discharge. Accordingly, when one observes from the side of the display surface H of a plasma display panel in which the phosphor layer 78 is disposed only on the glass substrate 79, the view is disturbed by the barriers 75 and 76. Thus, the viewing angle of display of a panel of the prior art is narrow and it becomes narrower as the fineness of the display image elements becomes higher. Further, the

surface area of the phosphor layer 78 in the unit
luminescent area EUj, i.e., the substantial luminescence
area, is small, which renders the brightness of display low
even when viewed from the right front side of the panel.

5 To solve this problem, in accordance with the present
invention, the phosphor layer is formed not only on the
surface of one substrate facing the display electrodes but
also on the side walls of the barrier. Further, on the
surface of the one substrate, the phosphor layer is also
10 formed on the address electrode, even if present.

In this construction, it is apparent that the viewing
angle of display is widened since the phosphor layers on the
side walls of the barriers contribute to the display and the
luminescent area is enlarged by the phosphor covering the
15 barriers and the address electrode.

Fig. 7 shows another example of a plasma display panel
according to the present invention which is very similar to
that shown in Fig. 2 except that the barriers 19 and 29 are
formed on both substrates 11 and 21, respectively. Fig. 8
20 shows a further example of a plasma display panel according
to the present invention which is very similar to that shown
in Fig. 2 except that the display electrodes have a
particular shape. In Figs. 7 and 8, the reference numbers
denoting parts corresponding to the parts of Fig. 2 are the
25 same as in Fig. 2.

In Fig. 7, the barriers 19 and 29 are made of a low
melting point glass and correspond to each other to define
the discharge cells 30, each barrier having a width of, for
example, 50 μm .

30 In the gap between the barriers 29 on the substrate 21,
address electrodes 22 having a predetermined width, for
example, 130 μm , are disposed, for example, by printing and
firing a pattern of a silver paste.

005050" 6684960

5 The phosphor layers 28 (28R, 28G and 28B) are coated on the entire surface of the glass substrate 21 including the side walls of the barriers 29 except for a top portion of the barriers 29 for contacting the member of the substrate 21, more specifically, a portion for contacting the protecting layer 18 of MgO in Figs. 2 and 7 and the barriers 19 in Fig. 7. Almost the entire surface of the unit luminescent area EU including the side walls of the barriers 29 and the surface of the address electrodes 22 are covered with the phosphor layers 28.

10

15 In the plasma display panel shown in Fig. 8, the display electrodes X' and Y' comprise transparent conductor strips 41' having cutouts K for localizing the discharge and strips of metal layers 42 having a constant width. The transparent conductor strips 41' are arranged with a predetermined discharge gap at a central portion of a unit luminescent area EU and larger widths at both end portions of the unit luminescent area EU to restrict the discharge so that discharge interference between the adjacent unit luminescent areas EU is prevented and, as a result, a wide driving voltage margin is obtained. The total width of the display electrodes X' and Y' and the gap therebetween is made to be not more than 70% of the width of the unit luminescent area EU or the pitch of the adjacent display electrodes.

20

25

On the rear glass substrate 21, an underlying layer 23, an address electrode 22, barriers 29 (29A and 29B) and phosphor layers 28 (28R, 28G and 28B) are laminated or formed.

30 The underlying layer 23 is of a low melting point glass, and is higher than that of the barriers 29, and serves to prevent deformation of the address electrodes 22 and the barriers 29 during thick film formation by absorbing a solvent from pastes for the address electrodes 22 and the

barriers 29. The underlying layer 23 also serves as a light reflecting layer by coloring, e.g., white by adding an oxide or others.

5 The address electrodes 22 are preferably of silver which can have a white surface by selecting suitable firing conditions.

10 The barriers 29 have a height almost corresponding to the distance of the discharge space 30 between the two substrates 11 and 21 and may be composed of low melting point glasses having different colors depending on the portions. The top portion 29B of the barriers 29 has a dark color, such as black, for improving the display contrast and the other portion 29A of the barriers 29 has a light color, such as white, for improving the brightness of the display. 15 This kind of barriers 29 can be made by printing a low melting point glass paste containing a white colorant, such as aluminum oxide or magnesium oxide, several times followed by printing a low melting point glass paste containing a black colorant and then firing both low melting point glass pastes together. 20

25 The phosphor layers 28 (R, G and B) are coated so as to cover the entire inner surface of the glass substrate 21 except for portions of the barriers 29 that are to make contact with the protecting layer 18 on the substrate 11 and portions nearby. Namely, the walls of the substrate 21 in the discharge space of the unit luminescent area EU, including the side walls of the barriers 29 and the address electrodes 22, are almost entirely covered with the phosphor layers 28. R, G and B denote red, green and blue colors of luminescence of the phosphor layers 28, respectively. 30

It is possible for an indium oxide or the like to be added to the phosphor layers 28 to provide conductivity in order to prevent stack of electric charge at the time of the

selective discharge and make the drive easily and stable depending on a driving method.

In this embodiment of Fig. 8, the phosphor layers 28 cover almost the entire surface of the barriers 29, which have an enlarged phosphor area compared to that of the embodiment of Fig. 7, so that the viewing angle and the brightness of the display are improved.

Further, since the underlying layer 23 and the barriers 29A are rendered a light color, such as white, the light that is emitted toward the background side is reflected by these light color members so that the efficiency of the utilization of light is improved, which is advantageous for obtaining a high display brightness.

Fig. 9 shows the brightness of panels at various view angles. The solid line shows a panel A in which the phosphor layers 28 also cover the side walls 29 of the barriers and the broken line shows a panel B in which the phosphor layers 28 do not cover the side walls 29 of the barriers. The panels A and B have the same construction but do not have the same phosphor coverage. It is seen from Fig. 9 that at the right front side of the display surface H (view angle of 0°), the brightness of the panel A is about 1.35 times that of the panel B, and in a wide viewing angle of -60° to $+60^\circ$, the brightness of the panel A is above or almost equal to that of the panel B obtained at the right front of the display surface H.

Fig. 10 shows the dependency of the display brightness on the view angle. The brightness of the display dependent on the view angle of a reflection type panel with phosphor layers on the side walls of the barriers, is shown to be even better than that of a transmission type panel, i.e., a panel in which the phosphor layers are disposed on a glass substrate of the side of the display surface EU.

As described before, it was found that the ratio of the total width of the display electrode pair X and Y including the width of the gap therebetween to the entire width of a unit luminescent area EU (hereinafter referred to as "electrode occupy ratio") should be not more than 70%, in order to avoid discharge interference between the adjacent lines L or display electrode pairs when there are no barriers between the adjacent lines L or display electrode pairs. Barriers between adjacent lines L or display electrode pairs are not necessary and can be eliminated if the electrode occupy ratio is selected to be not more than 70% of the entire width of a unit luminescent area EU.

Fig. 11 shows the firing voltage V_f and the minimum sustain voltage V_{sm} when the electrode occupy ratio is varied. As seen in Fig. 11, if the electrode occupy ratio exceeds over about 0.7, the firing voltage V_f is decreased and erroneous discharge between the adjacent lines of display electrodes may easily occur, but if the electrode occupy ratio is not more than about 0.7, the discharge is stable. If the electrode occupy ratio is not more than about 0.7, the minimum sustain voltage V_{sm} is also stable. If the electrode occupy ratio is more than about 0.7, the minimum sustain voltage V_{sm} is raised by discharge interference between adjacent lines L. Thus, a stable discharge operation or a wide operating margin can be obtained by selecting the electrode occupy ratio to be not more than about 0.7.

It is apparent that by eliminating barriers between adjacent unit luminescent areas defined along the extending direction of address electrodes, the effective display area and the brightness of the display can be improved and fabrication process becomes very easy.

Nevertheless, if the width of each of the display electrodes X and Y is less than about 20 μm , the electrodes

005060" 258459500

tend to be broken and the electrode occupy ratio should preferably be not less than about 0.15.

Furthermore, in the embodiments of Figs. 2 and 8, the discharge spaces are defined only by the barriers 29, in contrast to the embodiment of Fig. 7 where the discharge spaces are defined by the barriers 19 and 29 formed on both substrates 11 and 21. This permits the tolerance of the patterns of the barriers 29 to be enlarged significantly. For example, in the embodiment where the discharge spaces are defined by the barriers 19 and 29 formed on both substrates 11 and 21, if the unit luminescent area EU has a pitch of $220\text{ }\mu\text{m}$, the tolerance of the patterns of each of the barriers 19 and 29 should be very severe, \pm about $8\text{ }\mu\text{m}$. In contrast, if the barriers 29 are made only on one side, the tolerance of the patterns thereof may be about some hundreds μm and the pattern alignment is significantly easily made and even a cheap glass substrate having significant shrinkage during firing may be used.

Fig. 12 shows the relationships between the firing voltage V_f and, likewise, the minimum sustain voltage V_{sm} and the distance between the top of the barriers 29 and the protecting layer 18 of the opposite side substrate 11. The distance between the top of the barriers 29 and the protecting layer 18 of the opposite side substrate 11 was determined by measuring the difference in the height of the barriers 29 by the depth of focus through a metallurgical microscope. In the measured panel, the barriers 29 had top portions having a width larger than $15\text{ }\mu\text{m}$.

It is seen from Fig. 12 that if the distance between the top of the barriers 29 and the protecting layer 18 of the opposite side substrate 11 is more than $20\text{ }\mu\text{m}$, it is difficult to obtain a wide margin. Accordingly, if the distance is not more than $20\text{ }\mu\text{m}$, and preferably not more than $10\text{ }\mu\text{m}$, a wide margin can be obtained. To attain this,

it is preferred that the difference in height of the barriers be within $\pm 5 \mu\text{m}$.

Such a uniform height of barriers may be obtained by a method of forming a layer with a uniform thickness followed by etching or sand blasting the layer to form the barriers.

Further, it was found that the top portions of the barriers should preferably be made flat. Fig. 13 shows the relationship between the firing voltage V_f and minimum sustain voltage V_{sm} , and the width of the top flat portions of the barriers. The barriers having flat top portions were made by the above etching method. In Fig. 13, $V_f(N)$ represents the maximum firing voltage, $V_f(1)$ represents the minimum firing voltage, $V_{sm}(N)$ represents the maximum of the minimum sustain voltage, and $V_{sm}(1)$ represents the minimum of the minimum sustain voltage. As seen in Fig. 13, if the width of flat top portions of the barriers is not less than $7.5 \mu\text{m}$, and more preferably not less than $15 \mu\text{m}$, a wide margin can be obtained.

Such flat top portions of the barriers may be obtained by polishing the top portions of the barriers. This polishing also serves to obtain barriers with a uniform height.

In accordance with the present invention, the phosphor layers 28 are formed so as to cover the address electrodes 22 or A and side walls of the barriers so that the effective luminescent area is enlarged. In the conventional erase addressing method as shown in Fig. 5 for a panel as shown in Fig. 4, electric charges on the phosphors or the insulators are not sufficiently cancelled or neutralized and erroneous addressing may occur. Accordingly, a drive method for successfully treating the electric charges is required.

In accordance with an aspect of the present invention, this problem is solved by providing an ac plasma display panel in which the phosphor layers cover the address

electrodes with an erase address type drive control system by which once all of the image elements corresponding to the display electrodes are written, an erase pulse is applied to one of the pair of the display electrodes and simultaneously an electric field control pulse for neutralizing the applied erase pulse is selectively applied to the address electrodes.

In this erase address system, a discharge between the address electrodes 22 and the display electrodes X and Y does not occur and therefore, wall charges that prevent the addressing are not stacked on the phosphor layers 28 existing between the address electrodes 22 and the discharge spaces 30.

In another embodiment, there is provided a write address type drive control system by which in displaying a line corresponding to a pair of the display electrodes, a line select pulse is applied to one of the pair of the display electrodes and simultaneously an electric field address pulse for writing is selectively applied to the address electrodes.

In a further embodiment, the above write address type drive control system is constituted such that in displaying a line corresponding to a pair of the display electrodes, all of the image elements corresponding to the display electrodes are once subject to writing and erasing discharges to store positive electric charges on the phosphor layers and negative electric charges on the dielectric layer.

In these write address type drive control systems, the stack of charges on the address electrodes 22 or A permits addressing by a selective discharge pulse PA having a low voltage height V_a and by stacking positive charges on the address electrodes 22 or A prior to the addressing, the electric potential relationships between the respective

electrodes during the display period CH can be made advantageous in preventing ion bombardment to the phosphor layers 28.

Fig. 14 is a block diagram schematically showing the construction of an example of a plasma display device of the above embodiment. The plasma display device 100 comprises a plasma display panel 1 and a drive control system 2. The plasma display panel 1 and drive control system 2 are electrically connected to each other by a flexible printed board, not shown.

The plasma display panel 1 has a structure as shown in Fig. 2, 7 or 8. Fig. 15 schematically shows the electrode construction of the plasma display panel 1.

The drive control system 2 comprises a scan control part 110, an X electrode drive circuit 141 corresponding to the X display electrodes, a Y electrode drive circuit 142 corresponding to the Y display electrodes and an A electrode drive circuit 143 corresponding to the address electrodes A or 22, an A/D converter 120, and a frame memory 130.

The respective drive circuits 141 to 143 each comprise a high voltage switching element for discharge and a logic circuit for on-off operation of the switching element. The drive circuits apply predetermined drive voltages, i.e., the discharge sustain pulse PS, the writing pulse PW, erasing pulse PD and electric potential control pulse PC to respective electrodes X, Y and A in response to a control signal from the scan control part 110.

The A/D converter 120 converts the analog input signals, externally given as display information, to the image data of digital signals by quantization. The frame memory 130 stores the image data for one frame output from the A/D converter 120.

The scan control part 110 controls the respective drive circuits 141 to 143 based on the image data for one frame

stored in the frame memory 130, in accordance with the erase address system described below.

5 The scan control part 110 comprises a discharge sustain pulse generating circuit 111, a writing pulse generating circuit 112, an erasing pulse generating circuit 113, and an electric field control pulse generating circuit 114, which generate switching control signals corresponding to the respective pulses PS, PW, PD and PC.

10 In this plasma display device 100, the matrix display is performed by an erase address system in which selective erasing is carried out without selective discharge. Fig. 16 is the voltage waveform showing the driving method for the plasma display device 100.

15 For the plasma display device 100, in the initial address cycle CA in the line display period T, in the same manner as in the prior art as shown in Fig. 5, a discharge sustain pulse PS is applied to the display electrode Y and simultaneously a writing pulse is applied to the display electrode X. In Fig. 16, the inclined line in the discharge sustain pulse PS indicates that it is selectively applied to lines. By this operation, all surface discharge cells are made to be in a written state.

20 After the discharge sustain pulses PS are alternately applied to the display electrodes X and Y to stabilize the written states, and at an end stage of the address cycle CA, an erase pulse PD is applied to the display electrode Y and a surface discharge occurs.

25 The erase pulse PD is short in pulse width, $1\mu\text{s}$ to $2\mu\text{s}$. As a result, wall charges on a line as a unit are lost by the discharge caused by the erase pulse PD. However, by taking a timing with the erase pulse PD, a positive electric field control pulse PC having a wave height V_c is applied to address electrodes A or 22 corresponding to unit luminescent areas EU to be illuminated in the line. In Fig. 16, the

inclined line in the electric field control pulse PC indicates that it is selectively applied to the respective unit luminescent areas EU in the line.

5 In the unit luminescent areas EU where the electric field control pulse PC is applied, the electric field due to the erase pulse PD is neutralized so that the surface discharge for erase is prevented and the wall charges necessary for display remain. More specifically, addressing is performed by a selective erase in which the written
10 states of the surface discharge cells to be illuminated are kept.

In this addressing, since no discharge occurs between the address electrodes A or 22 and the display electrodes X and Y, wall charges that prevent the addressing are not
15 stacked on the phosphor layers 28 even if the phosphor layers 28 that are insulative exist on the address electrodes A or 22. Accordingly, erroneous illumination is prevented and an adequate display can be realized.

In the display period CH following the address cycle CA, the discharge sustain pulse PS is alternately applied to
20 the display electrodes X and Y to illuminate the phosphor layers 28. The display of an image is established by repeating the above operation for all line display periods.

Fig. 17 is a block diagram showing the construction of another example of a plasma display device 200; Fig. 18
25 shows the voltage waveform of a drive method of the plasma display device 200; and Figs. 19A to 19H are schematic sectional views of the plasma display panel showing the charge stack states at the timing (a) to (h) of Fig. 18.

30 The plasma display device 200 comprises a plasma display panel as illustrated in Fig. 2, 7 or 8 and a drive control system 3 for driving the plasma display device 200.

The drive control system 3 comprises a scan control part 210 in which a discharge sustain pulse generating

circuit 211 and a selective discharge pulse generating circuit 214 are provided.

In this plasma display device 200, the matrix display is performed by a write addressing system.

5 Referring to Fig. 18, in the display of a line, a discharge sustain pulse PS is selectively applied to the display electrode Y and a selective discharge pulse PA is selectively applied to the address electrodes A or 22 corresponding to unit luminescent areas EU to be illuminated
10 in the line depending on the image. By this, opposite discharges between the address electrodes A or 22 and the display electrode Y or selective discharges occur, so that the surface discharge cells C are made into written states and the addressing finishes.

15 In this example, however, prior to the addressing, the charge stack state for alleviating the ion bombardment damage to the phosphor layers 28 has been formed in the manner as described below.

20 First, at a normal state, a positive discharge sustain voltage Vs has been applied to the display electrodes X and Y so that the pulse base potential of the display electrodes X and Y is made positive.

25 At an initial stage of the address cycle CA, a writing pulse PW is applied to the display electrode X so as to make the potential thereof a predetermined negative potential, -Vw.

30 As a result, as shown in Fig. 19A, a positive charge, i.e., ions of discharge gas, having a polarity opposite to that of the applied voltage, is stacked on the portion of the dielectric layer 17 above the display electrode X (hereinafter referred to as "portion above the display electrode X") and a negative charge is stacked on the portion of the dielectric layer 17 above the display electrode Y (hereinafter referred to as "portion above the

display electrode Y"). As a result of the relative electric field relationships of the address electrodes A or 22 and the display electrodes X and Y, a negative charge is stacked on a portion of the phosphor layers 28 that covers the address electrodes A or 22 and opposes the display electrode X and a positive charge is stacked on a portion of the phosphor layers 28 that opposes the display electrode Y.

Next the display electrode X is returned to the pulse base potential and the display electrode Y is made to be at the ground potential, i.e., zero volts. Namely, a discharge sustain pulse PS is applied to the display electrode Y. At this time, as shown in Fig. 19B, the polarities of the charges of the portions above the display electrodes X and Y are reversed by the surface discharge and the charge on the portion of the phosphors 28 above the address electrode A or 22 that opposes the display electrode X is reversed to positive.

Then, after a discharge sustain pulse PS is applied to the display electrode X, the display electrode Y is returned to the pulse base potential to reverse the polarities of the charges on the portions above the display electrodes X and Y, as shown in Fig. 19C.

While a discharge sustain pulse PS is applied to the display electrode X or the display electrode X is the ground potential, a discharge sustain pulse PS is also applied to the display electrode Y and the display electrodes X and Y are returned to the pulse base potential in this order with a very short timing difference (t) of about $1 \mu s$. As a result, a surface discharge occurs at the time when the display electrode X is returned to the pulse base potential, but after the very short time (t); the display electrodes X and Y attain the same potential; and the surface discharge immediately stops so that the charges on the portions above the display electrodes X and Y are lost.

Nevertheless, then, since the pulse base potential is positive and a potential difference appears between the display electrodes X and Y and the address electrodes A or 22, a negative charge is uniformly stacked on the portions above the display electrodes X and Y and a positive charge is uniformly stacked on the portions above the address electrodes A or 22, as shown in Fig. 19D. In this state, the cells are in the erased state.

In this way, the charge stack state is formed for all surface discharge cells C corresponding to one line. At an end stage of the address cycle CA, a surface discharge occurs between the address electrodes A or 22 and the display electrode Y. As a result of the opposite discharge, a positive charge is stacked on the portion above the display electrode Y and negative charges are stacked on the portion above the display electrode X and on the portions above the address electrodes A or 22.

In the following display cycle CH, a discharge sustain pulse PS is alternately applied to the display electrodes X and Y to illuminate the phosphor layers 28, during which the surface discharge occurs at every instance when one of the display electrodes X and Y becomes a negative potential to the pulse base potential, and at the time of generating the surface discharge, the address electrodes A or 22 in the state of capacitor coupling with the display electrodes X and Y become a positive potential relative to the negative potential of the display electrodes X and Y. As a result, movement of positive charges, i.e., ions, toward the address electrodes A or 22 is prevented so that the ion bombardment to the phosphors 28 is alleviated.

In the display cycle CH, the polarities of the charges on the portions above the display electrodes X and Y and the address electrodes A or 22 are changed as shown in Figs. 19F to 19H.

005060" 26345950

In the write address system, since the address finishes by the discharge at a rising edge of the selective discharge pulse PA, in contrast to the erase address system where the address finishes by the self-erase discharge immediately after the selective discharge pulse PA, disadvantageous effects of the stack of charges on the portions above the address electrodes A or 22 do not appear and the address is stabilized even by the wall charges when the selective discharge pulse PA has a voltage height V_a that is low.

The full color display can be attained by performing the above operation to each of the three primary color luminescent areas EU. The graded display can be attained by adequately selecting the number of the surface discharge during respective divided periods.

In the above embodiments, the discharge can be stabilized even when the phosphor layers 28 are formed to cover the address electrodes A or 22 and thus improvement of the brightness of display and the viewing angle can be attained. The results are shown in Figs. 9 and 10.

The phosphor layers are typically coated on a substrate by a screen printing method, which is advantageous in productivity compared to the photolithography method and effectively prevents inadvertent mixing of different color phosphors. Conventionally, the typical phosphor paste contains a phosphor in an amount of 60 to 70% by weight and a square squeezer is used at a set angle of 90° .

Nevertheless, in a preferred embodiment of the present invention, the phosphor layers 28 are coated not only on the surface of a substrate 21 but also on side walls of barriers 29 having a height of, for example, about $100\ \mu\text{m}$, which necessitates the dropping of a phosphor paste from a screen, set at a height of about $100\ \mu\text{m}$ above the surface of the substrate 21, onto the surface of the substrate 21 and makes a uniform printing area and thickness difficult. The

nonuniform printed area and thickness of the phosphors degrade the display quality, such as causing uneven brightness or color tones, and make the discharge characteristic unstable.

5 Fig. 20 shows an ideal coating, i.e., the uniform coating of a phosphor layer 28 on the side walls of barriers 29 and on the substrate 21 and the address electrode 22.

10 The present invention solves this problem by a process comprising forming barriers on a substrate, screen printing phosphor pastes so as to fill the cavity formed between the barriers on the substrate with the phosphor pastes and then firing the phosphor pastes so as to reduce the volume of the phosphor pastes, forming recesses between the barriers on the substrate, and forming phosphor layers covering, almost
15 entirely, the side walls of the barriers and the surface of the substrate. In this process, the amount of the filled phosphor pastes is determined by the volume of the cavity between the barriers on the substrate and is therefore constant. Thus, a uniform printing or coating can be made.

20 The thickness of the phosphor layer obtainable after firing is almost in proportion to the content of the phosphor in the phosphor paste, as shown in Fig. 21. On the other hand, the brightness of the display is increased as the thickness of the phosphor layer is thickened up to about
25 60 μm and a practically adequate brightness is obtained by a thickness of the phosphor layer of about 10 μm or more. On the other hand, as the thickness of the phosphor layer is increased, the selective discharge initialization voltage is also increased and if the thickness of the phosphor layer is
30 over 50 μm , selective discharge becomes difficult in a drive voltage margin. Accordingly, the thickness of the phosphor layer is preferably 10 to 50 μm . This suggests that a phosphor paste having a content of a phosphor of 10 to 50% by weight be used.

Referring to Figs. 22A to 22C, first, on a glass substrate 21, address electrodes 22 of, e.g., silver about 60 μm thick and barriers 29 of a low melting point glass about 130 μm high are formed by the screen printing method, respectively. Here, for example, a screen mask in which openings having a width, for example, about 60 μm are arranged at a constant pitch (p), for example, 220 μm is used for printing a silver paste and a glass paste to form the address electrodes 22 and the barriers 29. In this case, the address electrodes 22 would have a width of about 60 to 70 μm and the barriers 29 would have a bottom width (w_1) of about 80 μm and a top width (w_2) of about 40 μm .

As shown in Fig. 22A, a screen 80, in which openings 81 having a predetermined width are formed at a pitch triple the pitch (p) is arranged over the glass substrate 21 so as to contact the tops of the barriers 29 and adequately align the glass substrate 21.

Then a phosphor paste 28a comprising a phosphor having a predetermined luminescent color, for example, red, and a vehicle is dropped through the openings 81 into the space between the barriers 29. The used phosphor paste 28a has a content of phosphor of 10 to 50% by weight, in order to make the thickness of the phosphor layer 28 not more than 50 μm . The vehicle of the phosphor paste 28a may comprise a cellulose or acrylic resin thickener and an organic solvent such as alcohol or ester.

In addition, the phosphor paste 28a is pushed as much as possible toward the space between the barriers 29, in order to substantially fill the space. To attain this, a square squeezer, or squeegee, 82 is used and the set angle θ is set to 70 to 85°.

The square squeezer 82 is, for example, a hard rubber in the form of a bar having a rectangular and usually square cross section attached to a holder 83. A practical square

squeezer 82 has a length (d) of the diagonal line in the cross section of about 10 to 15 mm.

5 The set angle θ of the square squeezer 82 is an angle formed by a line connecting the contact point and the center of the square squeezer 82 with the surface of the screen mask 80 in the direction of movement of the square squeezer 82 from the contact point, when the square squeezer 82 makes contact with the screen mask 80 at a point and moves in the direction of the arrow M1 while maintaining contact. When 10 the set angle θ is 70° to 85° , a cross angle of the surface of the screen mask 80 and the surface facing the screen mask 80 of the square squeezer 82 is 25° to 40° , which is smaller than the conventional value of $\alpha=45^\circ$ when the set angle θ is conventionally set to $\theta=90^\circ$. As a result, a force applied to 15 the phosphor paste 28a by the square squeezer 82 is increased and a larger amount of the phosphor paste 28a can be extruded from the openings 81 into the spaces between the barrier, than is done conventionally.

20 Then, the other phosphor pastes, for green (G) and blue (B) luminescences, are also filled in the predetermined spaces between the barriers 29 in order. The phosphor pastes have a content of phosphor of 10 to 50% by weight. Thus, all spaces between the barriers 29 are filled with predetermined phosphor pastes 28a (R, G and B), as shown in Fig. 22B.

25 The phosphor pastes 28a (R, G and B) are then dried and fired at a temperature of about 500 to 600°C . Thereby, the vehicle evaporates and the volumes of the phosphor pastes 28a are decreased significantly, so that the phosphor layers 28 having almost ideal forms as shown in Fig. 22C are 30 obtained.

Of course, the content of the phosphor in the phosphor paste 28a may be adequately selected depending on the volume of the space between the barriers, the area of the inner surface of the substrate and barrier side wall surfaces

surrounding and defining the space, the desired brightness and discharge characteristics, and other conditions.

Fig. 23 is a perspective view of a plasma display panel in which H denotes the display surface, EH denotes the display area or discharge area, 11 and 21 denote the glass substrates, and 22 denotes the address electrodes. The display electrodes X and Y are similarly formed but not shown. After the predetermined elements are formed thereon, the glass substrates 11 and 21 are faced (i.e., disposed in facing, or opposed, relationship) and assembled together, sealed along the periphery, evacuated inside and filled with a discharge gas. This panel is electrically connected with an external drive circuit, not shown, through a flexible printed board or the like, not shown. The ends of the respective electrodes are enlarged and each of the glass substrates 11 and 21 extends at opposite ends 11', 11" and 21', 21" thereof from the opposite sides 21a, 21b and 11a, 11b, respectively, of the other one of the substrates, so that the enlarged portions of the electrodes are disposed on the extended substrate portions for connecting with outer leads.

Now referring to Figs. 24A and 24B, the address electrodes 22 and barriers 29 on the glass substrate 21 are typically formed in a process comprising the steps of first, printing patterns 22a of the address electrodes of, e.g., a silver paste through a screen printing step, second, repeatedly printing patterns 29a of the barriers of, e.g., a glass paste, until forming a predetermined thickness through a screen printing step, and then firing the patterns 22a and 29a at the same time, i.e., simultaneously. The patterns 22a of the silver paste, instead, may be fired before the printing of the patterns 29a of the glass paste.

In this process, it is difficult to make an alignment of the address electrodes 22 and barriers 29 because of size

dispersion of the printing mask and it is difficult to manufacture a very fine and large-sized panel.

Printing masks have a size dispersion of mask patterns caused by the limitation of mask manufacturing processes.

5 For example, if the address electrodes 22 have a length L of 40cm, the size dispersion of the mask patterns, from one end strip pattern to the other end strip pattern, may be \pm about 50 μ m. The total of these size dispersions of the printing masks for the address electrodes 22 and the barriers 29 may
10 be 100 μ m at maximum. The size dispersion becomes larger as the printing mask becomes larger.

Accordingly, if one end of the glass substrate 21 is used as the alignment reference, the difference of the pitch of the printing mask for the barriers 29 is added with the
15 difference of the pitch of the printing mask for the address electrodes 22 at the other end of the glass substrate 21 and accordingly, the alignment between the address electrodes 22 and the barriers 29 is degraded significantly. Therefore, the alignment of the printing masks is finely adjusted so as
20 to obtain a uniform distribution of the patterns, but it is not easy to avoid overlaps between the address electrodes 22 and the barriers 29. If the size dispersion of the patterns is large, the fine adjustment of the masks cannot be effective.

25 The present invention solves the above problem by a process of printing a material for main portions of the address electrodes with a printing mask, separately printing a material for end portions of the address electrodes for connecting with outer leads, and then printing a material
30 for the barriers with the same printing mask.

Since the patterns of the main portions of the address electrodes and the patterns of the barriers are printed using the same printing mask, the pitches of the main portions of the address electrodes and the corresponding

005060" 56345900

itches of the barriers cannot be different, irrespective of the size dispersion of the patterns of the printing mask. Accordingly, the main portions of the address electrodes and the barriers can be easily aligned by simply parallel shifting the printing mask a certain distance.

Now referring to Fig. 25A, silver paste patterns 22Ba for connecting portions 22B of address electrodes 22 are printed on a glass substrate 21 with a printing mask, not shown. The connecting portions 22B of address electrodes 22 are disposed outside the display area EH (Fig. 23) and comprise, for example, enlarged portions 91 for external connection and reduced portions 92 for connecting with the main portions of the address electrodes 22, as shown in Fig. 25A.

In this example, the connecting portions 22B are arranged outside the display area EH, for alternate ones of the address electrodes 22 on respective, opposite sides of the substrate 21 (22). That is, the printing mask has such a pattern that the connecting portions 22B are arranged alternately on respective, opposite sides at a pitch of double the pitch of the address electrodes 22. The width w_{11} of the reduced portions 92, at an end of the connecting portions 22B for connecting with the main portions 22A of the address electrodes 22, is made larger than the width w_{10} of the main, or enlarged, portions 22A of the address electrodes 22, thereby making alignment of these portions 92 and 22A easy.

After the silver paste 22Ba is dried, silver paste patterns 22Aa for the main portions 22A of the address electrodes 22 are printed, using a printing mask as shown in Fig. 25B, on the glass substrate 21 so as to partially overlap with the silver paste patterns 22Ba, as shown in Fig. 25C.

The main portions 22A of the address electrodes 22 include corresponding, main discharge portions, defining the discharge cells, in the display area EH and minor portions, extending outside the display area EH from the discharge portion.

The printing mask 90 has a mask pattern comprising a plurality of strip openings 95 for the main portions 22A of the address electrodes 22. The openings 95 have a width w_{10} of, e.g., 60 μm , and a pitch of, e.g., 220 μm . These sizes are design sizes and therefore the actual size may be slightly different depending on manufacturing requirements.

Alternate ones of the openings 95 extend, at first ends 95, from the ends 95" of adjacent, alternate, openings 95 by a distance (d) to make the alignment with the corresponding connecting portions 22B or the silver paste patterns thereof 22Ba easy.

Then, the printing mask 90 is cleaned by removing the adhered silver paste with a solvent or the like. Again, and using the same printing mask 90, low melting point glass paste patterns 29a for the barriers 29 are printed in a lamination manner several times, as shown in Fig. 25D.

At this time, the printing mask 90 can be placed at a location that is parallel to, but shifted by half of the pitch (p) from, the location at which it was placed for printing the main portions 22Aa of the address electrodes, with the glass substrate 21 as a reference. Accordingly, the mask alignment problems can be substantially eliminated.

Then, the silver paste patterns 22Aa and 22Ba and the low melting point glass paste patterns 29a are fired together (i.e., at the same time, or simultaneously) to form the address electrodes 22 and the barriers 29, as shown in Fig. 25D. Fig. 25E corresponds to a portion BB enclosed by the dash-dot-line in Fig. 25 D .

When the width W_{10} of the openings 95 of the printing mask 90 is $60\text{ }\mu\text{m}$, the practically obtained address electrodes 22 have a width of about 60 to $70\text{ }\mu\text{m}$, and the practically obtained barriers 29 have a width of about $80\text{ }\mu\text{m}$.

In the above example, since a display is not disturbed by overlap of the barriers 29 with the connecting portions 22B, the width of the reduced portions 92 of the connecting portions 22B may be sufficiently enlarged, for example, to the same width as that of the enlarged portions 91, so that the alignment of the connecting portions 22B and the main portions 22A of the address electrodes 22 can be made easier.

It is apparent that the materials for the address electrodes or the barriers may vary.

CLAIMS

1. A full color surface discharge type plasma display device comprising

5 pairs of lines of display electrodes, each pair of lines of display electrodes being parallel to each other and constituting an electrode pair for surface discharge,

10 lines of address electrodes insulated from the display electrodes and running in a direction intersecting the lines of display electrodes,

15 three phosphor layers different from each other in luminescent color facing the display electrodes and arranged in a successive order of the three phosphor layers along the extending lines of the display electrodes, and

 a discharge gas in a space between said display electrodes and said phosphor layers,

20 wherein the adjacent three phosphor layers of said three different luminescent colors in a pair of lines of display electrodes define one image element of a full color display.

25 2. A device according to claim 1 wherein said image element has an area of almost a square and each of said three phosphor layers has a rectangular shape that is obtained by dividing said square of the image element and is long in a direction perpendicular to said lines of display electrodes.

30 3. A device according to claim 1 wherein each of the lines of said display electrodes comprises a combination of a transparent conductor line and a metal line in contact with the transparent conductor line and having a width narrower than that of the transparent conductor line and is disposed on the side of a viewer
35 compared with the phosphor layers.

 4. A device according to claim 3 wherein said transparent conductor lines have partial cutouts in

005060" E634E960

such a shape that the surface discharge is localized to a portion between the display electrodes without the cutout in each unit luminescent area.

5 5. A device according to claim 1 wherein the total width of a pair of the display electrodes and a gap for discharge formed between said pair of the display electrodes is less than 70 % of a pitch of said pairs of display electrodes.

10 6. A device according to claim 1 further comprising barriers standing on a substrate and dividing and separating said space between said display electrodes and said phosphor layers into cells corresponding to respective phosphor layers.

15 7. A device according to claim 6 wherein said barriers have side walls and said phosphor layers extend to and almost entirely cover the side walls of said barriers.

20 8. A device according to claim 7 wherein said address electrodes exist on a side of the substrate opposite to said display electrodes and said address electrodes are entirely covered with said phosphor layers.

25 9. A device according to claim 7 further comprising a substrate and an underlying layer of a low melting point glass containing a light color colorant formed on said substrate and said address electrodes are formed on said underlying layer.

30 10. A device according to claim 7 wherein at least part of said barriers comprises a low melting point glass containing a light color colorant.

35 11. A device according to claim 7 wherein said barriers comprises a low melting point glass containing a dark color colorant in a top portion thereof and a low melting point glass admixed with a light color colorant in the other portion thereof.

12. A full color surface discharge plasma display device comprising

005060" E5845960

first and second substrates facing and parallel to each other for defining a space in which a discharge gas is filled,

5 pairs of lines of display electrodes formed on the first substrate facing the second substate, each pair of lines of display electrodes being parallel to each other and constituting an electrode pair for surface discharge,

10 a dielectric layer over the display electrodes and the first substarate,

lines of address electrodes formed on the second substate facing the first substrate and running in a direction intersecting the lines of display electrodes,

15 three phosphor layers different from each other in luminescent color formed on the second substrate in a successive order of said three luminescent colors along the extending lines of the display electrodes, the phosphor layers entirely covering the address electrodes, and

20 barriers standing on the second substrate to divide and separate said discharge space into cells corresponding to respective phosphor layers, the barriers having side walls,

25 wherein the adjacent three phosphor layers of said three different luminescent colors in a pair of lines of display electrodes define one image element of a full color display and said phosphor layers extend to the side walls of said barriers to cover almost the entire surfaces of the side walls of said barriers.

30 13. A device according to claim 12 further comprising a erase address type drive control system by which once all of the image elements corresponding to the display electrodes are written, an erase pulse is applied to one of the pair of the display electrodes and simultaneously an electric field control pulse for neutralizing the applied erase pulse is selectively

35

005060" 65045960

applied to the address electrodes.

14. A device according to claim 12 further comprising a write address type drive control system by which in displaying a line corresponding to a pair of the display electrodes, a discharge display pulse is applied to one of the pair of the display electrodes and simultaneously an electric field control pulse for writing is selectively applied to the address electrodes.

15. A device according to claim 14 wherein said write address type drive control system is constituted such that in displaying a line corresponding to a pair of the display electrodes, once all of the image elements corresponding to the display electrodes are subject to writing and erasing discharges, to store positive electric charges above said phosphor layers and negative electric charges above said dielectric layer, an electric discharge display pulse is applied to one of the pair of the display electrodes to make said one of the pair of the display electrodes negative in electric potential to the other of the pair of the display electrodes, and an electric discharge pulse is selectively applied to the address electrodes to make the address electrodes positive in electric potential to said one of the pair of the display electrodes.

16. A device according to claim 12 wherein each of the lines of said display electrodes comprises a combination of a transparent conductor line and a metal line in contact with said transparent conductor line and having a width narrower than that of the transparent conductor line and is disposed on the side of a viewer compared to the phosphor layers.

17. A device according to claim 12 wherein said barriers extend from and are fixed only to said second substrate.

18. A device according to claim 12 wherein each of said barriers is formed by a first barrier portion

formed on one of the substrates and a second barrier portion formed on the other of the substrates.

19. A device according to claim 17 wherein said barriers have a difference in height within 10 μ m.

20. A device according to claim 19 wherein said barriers have a flat top surface.

21. A full color surface discharge plasma display device comprising

first and second substrates facing and parallel to each other for defining a space in which a discharge gas is filled, the first substrate being disposed on a side of a viewer,

pairs of lines of display electrodes formed on the first substrate facing the second substate, each pair of lines of display electrodes being parallel to each other and constituting an electrode pair for surface discharge, each of the display electrodes comprising a combination of a transparent conductor line and a metal line in contact with said transparent conductor line and having a width narrower than that of the transparent conductor line,

a dielectric layer over the display electrodes and the first substarate,

lines of address electrodes formed on the second substate facing the first substrate and running in a direction intersecting the lines of display electrodes,

barriers standing on the second substrate inparallel to said address electrodes for dividing said discharge gas space into cells, the barriers having side walls, and

three phosphor layers different from each other in luminescent color formed on the second substrate in a successive order of said three luminescent colors along the extending lines of the display electrodes, the phosphor layers entirely covering the address electrodes and extending to the

side walls of said barriers to cover almost entire surfaces of the side walls of said barriers,

wherein the adjacent three phosphor layers of said three different luminescent colors in a pair of lines of display electrodes define one image element of a full color display.

22. A device according to claim 21 wherein the total width of said display electrodes and a gap for discharge formed therebetween is less than 70 % of a pitch of said pairs of display electrodes.

23. A device according to claim 21 wherein said barriers comprise a top portion of a low melting point glass containing a dark color colorant and the other portion of a low melting point glass containing a light color colorant.

24. A process for manufacturing a full color surface discharge plasma display device as set forth in claim 12, in which said address electrodes and said barriers are parallel to each other and said address electrodes comprise a main portion for display parallel to said barriers and a portion at an end of said main portion for connecting outer leads, said process comprising the steps of:

printing a material for forming said main portions of the address electrodes using a printing mask,

printing a material for forming said outer lead-connecting portions, and

printing a material for forming said barriers using said printing mask used for printing said material for forming the main portions of the address electrodes.

25. A process for manufacturing a full color surface discharge type plasma display device as set forth in claim 12, said process comprising the steps of:

forming said barriers on said second substrate,

almost filling gaps between said barriers
above said second substrate with a phosphor paste,

firing said phosphor paste to reduce the
volume of said phosphor paste and form recesses between
5 said barriers and to form a phosphor layer covering
almost the entire surfaces of side walls of said
barriers and covering surfaces of said second substrate
between said barriers.

26. A process according to claim 25 wherein said
10 phosphor paste comprises a phosphor in an amount of 10
to 50 % by weight.

27. A process according to claim 25 wherein said
filling of said phosphor paste is performed by screen
printing said phosphor paste into said gaps with a
15 square squeezer at a set angle of 70 to 85 degrees.

005060" 66345960

20

25

30

35

ABSTRACT OF THE DISCLOSURE

A full color three electrode surface discharge type plasma display device that has fine image elements and is large and has a bright display. The three primary color luminescent areas are arranged in the extending direction of the display electrode pairs in a successive manner and an image element is composed by the three unit luminescent areas defined by these three luminescent areas and address electrodes intersecting these three luminescent areas. Further, phosphors are coated not only on a substrate but also on the side walls of the barriers and on address electrodes. The manufacturing processes and operation methods of the above constructions are also disclosed.

005060" 06345960

$\frac{1}{19}$
Fig. 1




Fig. 2




Fig.3A PRIOR ART





Fig.3B PRIOR ART



005060" E6845960

Fig. 4 PRIOR ART




Fig. 5 PRIOR ART




Fig. 6
PRIOR ART




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig.1 1




Fig.12




Fig.13




Fig.14




Fig. 15





Fig. 16



12/19

Fig.17





Fig.18















Fig.20*Fig.21*

Fig. 22A




Fig. 22B




Fig. 22C




Fig. 23




Fig. 24A

PRIOR ART




Fig. 24B

PRIOR ART




Fig. 25A




Fig. 25B




Fig. 25C




Fig. 25D





Fig. 25E



COMBINED DECLARATION/POWER OF ATTORNEY FOR UTILITY/DESIGN PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

FULL COLOR SURFACE DISCHARGE TYPE PLASMA DISPLAY DEVICE

the specification of which (check one) ☒ is attached hereto ☐ was filed on _____
as U.S. Application Serial No. _____ and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in §1.56. I hereby claim foreign priority benefit(s) under 35 U.S.C. §119 of any foreign application(s) for patent or inventor's certificate listed below and have the application on which priority is claimed.

Prior Foreign Application(s)

Priority Claimed

04-012976 (Pat. Appln.) Japan
(Number) (Country)

28/January/1992
Day/Month/Year Filed

☒ []
Yes No

04-106953 (Pat. Appln.) Japan
(Number) (Country)

24/April/1992
Day/Month/Year Filed

☒ []
Yes No

See page 3 for additional Foreign Applns.

I hereby claim the benefit under 35 U.S.C. §120 of any U.S. application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application(s) in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

POWER OF ATTORNEY:

As a named inventor, I hereby appoint the following attorneys and agent: James D. Halsey, Jr., Reg. No. 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; Gene W. Stockman, 21,021; John C. Garvey, 28,607; J. Randall Beckers, 30,358; James H. Marsh, Jr., 24,533; Auzville Jackson, Jr., 17,306; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Carla M. Krivak, 30,956; Matthew J. Bussan, 33,614; Daniel W. Juffernbruch, 33,122; Harold C. McGurk, IV, 34,964; Jon M. Jurgovan, 34,633, and Irah H. Donner, P35,120 to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. Send correspondence to: STAAS & HALSEY, 1825 K Street, N.W., Suite 816, Washington, D.C., 20006, and direct telephone calls to: (202) 872-0123

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. §1001, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Tsutae Shinoda

Inventor's Signature Tsutae Shinoda Date January 18, 1993

Residence Kawasaki-shi, Kanagawa, Japan

Citizenship Japanese

Post Office Address c/o FUJITSU LIMITED, 1015, Kamikodanaka, Nakahara-ku, Kawasaki-shi,
Kanagawa 211, Japan

Full name of second joint inventor, if any Noriyuki Awaji

Second Inventor's Signature Noriyuki Awaji Date January 18, 1993

Residence Kawasaki-shi, Kanagawa, Japan

Citizenship Japanese

Post Office Address c/o FUJITSU LIMITED, 1015, Kamikodanaka, Nakahara-ku, Kawasaki-shi,

(Supply similar information and signature lines for third and subsequent joint inventors.)

Kanagawa 211, Japan

Full name of third joint inventor, if any Shinji Kanagu

Inventor's Signature Shinji Kanagu Date January 18, 1993

Residence Kawasaki-shi, Kanagawa, Japan

Citizenship Japanese

Post Office Address c/o FUJITSU LIMITED, 1015, Kamikodanaka, Nakahara-ku, Kawasaki-shi, Kanagawa 211, Japan

Full name of fourth joint inventor, if any Tatsutoshi Kanae

Inventor's Signature Tatsutoshi Kanae Date January 18, 1993

Residence Kawasaki-shi, Kanagawa, Japan

Citizenship Japanese

Post Office Address c/o FUJITSU LIMITED, 1015, Kamikodanaka, Nakahara-ku, Kawasaki-shi, Kanagawa 211, Japan

Full name of fifth joint inventor, if any Masayuki Wakitani

Inventor's Signature Masayuki Wakitani Date January 18, 1993

Residence Kawasaki-shi, Kanagawa, Japan

Citizenship Japanese

Post Office Address c/o FUJITSU LIMITED, 1015, Kamikodanaka, Nakahara-ku, Kawasaki-shi, Kanagawa 211, Japan

Full name of sixth joint inventor, if any Toshiyuki Nanto

Inventor's Signature Toshiyuki Nanto Date January 18, 1993

Residence Kawasaki-shi, Kanagawa, Japan

Citizenship Japanese

Post Office Address c/o FUJITSU LIMITED, 1015, Kamikodanaka, Nakahara-ku, Kawasaki-shi, Kanagawa 211, Japan

Full name of seventh joint inventor, if any Mamoru Miyahara

Inventor's Signature Mamoru Miyahara Date January 18, 1993

Residence Kawasaki-shi, Kanagawa, Japan

Citizenship Japanese

Post Office Address c/o FUJITSU LIMITED, 1015, Kamikodanaka, Nakahara-ku, Kawasaki-shi, Kanagawa 211, Japan

Full name of eighth joint inventor, if any _____

Inventor's Signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____

| | | | |
|-------------------------|-----------|------------------------|-----------------------------------------------------------------------------------------|
| 04-96203 (Pat. Appln.) | Japan | 16/April/1992 | Priority Claimed <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| (Number) | (Country) | (Day/Month/Year Filed) | |
| 04-106955 (Pat. Appln.) | Japan | 24/April/1992 | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| (Number) | (Country) | (Day/Month/Year Filed) | |
| 04-110921 (Pat. Appln.) | Japan | 30/April/1992 | <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No |
| (Number) | (Country) | (Day/Month/Year Filed) | |
| _____ | _____ | _____ | <input type="checkbox"/> Yes <input type="checkbox"/> No |
| (Number) | (Country) | (Day/Month/Year Filed) | |
| _____ | _____ | _____ | <input type="checkbox"/> Yes <input type="checkbox"/> No |
| (Number) | (Country) | (Day/Month/Year Filed) | |
| _____ | _____ | _____ | <input type="checkbox"/> Yes <input type="checkbox"/> No |
| (Number) | (Country) | (Day/Month/Year Filed) | |
| _____ | _____ | _____ | <input type="checkbox"/> Yes <input type="checkbox"/> No |
| (Number) | (Country) | (Day/Month/Year Filed) | |

Full name of ninth joint inventor, if any _____

Inventor's signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____

Full name of tenth joint inventor, if any _____

Inventor's signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____

Full name of eleventh joint inventor, if any _____

Inventor's signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____

Full name of twelfth joint inventor, if any _____

Inventor's signature _____ Date _____

Residence _____

Citizenship _____

Post Office Address _____